

DUMPSBOSS.COM

200-550

Zend 200-550

Version Demo

Total Demo Questions: 15

Total Premium Questions: 223

Buy Premium PDF

<https://dumpsboss.com>

support@dumpsboss.com

dumpsboss.com

QUESTION NO: 1

What is the output of the following code? class A { public \$a = 1;

public function __construct(\$a) { \$this->a = \$a; }

public function mul() { return function(\$x) {

return \$this->a*\$x;

};

}

}

\$a = new A(2); \$a->mul = function(\$x) {

return \$x*\$x;

};

\$m = \$a->mul(); echo \$m(3);

A. 9

B. 6

C. 0

D. 3

ANSWER: B**QUESTION NO: 2**

What is the output of this code?

\$world = 'world'; echo <<<'TEXT' hello \$world TEXT;

A. hello world

B. hello \$world

C. PHP Parser error

ANSWER: C

QUESTION NO: 3

Which of the following rules must every correct XML document adhere to? (Choose 2)

- A. It has to be well-formed.
- B. It has to be valid.
- C. It has to be associated to a DTD.
- D. It may only contain UTF-8 encoded characters.

ANSWER: A B**QUESTION NO: 4 - (SIMULATION)**

SIMULATION

What is the output of the following code? function increment (\$val)

```
{  
++$val; }  
$val = 1; increment ($val); echo $val;
```

ANSWER: 1**QUESTION NO: 5**

You need to escape special characters to use user input inside a regular expression. Which functions would you use? (Choose 2)

- A. addslashes()
- B. htmlentities()
- C. preg_quote()
- D. regex_quote()
- E. quote_meta()

ANSWER: C E**QUESTION NO: 6**

How do you allow the caller to submit a variable number of arguments to a function?

- A. Using a prototype like function test(... \$parameters).
- B. Using a prototype like function test() and the function func_get_args() inside the function body.
- C. Using a prototype like function test(\$parameters[]).
- D. Using a prototype like function test() and the function get_variable_args() inside the function body.
- E. This is not possible in PHP.

ANSWER: B

QUESTION NO: 7 - (SIMULATION)

SIMULATION Which DOMElement property provides a reference to the list of the element's children?

ANSWER: childNodes

QUESTION NO: 8

What is the result of the following code?

```
define('PI', 3.14);  
  
class T  
{  
    const PI = PI;  
}  
  
class Math  
{  
    const PI = T::PI;  
}  
  
echo Math::PI;
```

- A. Parse error
- B. 3.14
- C. PI
- D. T::PI

ANSWER: B**QUESTION NO: 9**

What is the output of the following code?

```
class Number { private $v; private static $sv = 10;
public function __construct($v) { $this->v = $v; } public function mul() { return static function ($x) {
return isset($this) ? $this->v*$x : self::$sv*$x;
};
}}
$one = new Number(1); $two = new Number(2);
$double = $two->mul();
$x = Closure::bind($double, null, 'Number'); echo $x(5);
```

- A. 5
- B. 10
- C. 50
- D. Fatal error

ANSWER: C**QUESTION NO: 10**

Under what condition may HTTP headers be set from PHP if there is content echoed prior to the header function being used?

- A. headers_sent() returns true
- B. Output buffering is enabled
- C. The client supports local buffering
- D. The webserver uses preemptive mode

ANSWER: B**QUESTION NO: 11**

Which of the following are NOT acceptable ways to create a secure password hash in PHP?

(Choose 2)

- A. md5()
- B. hash_pbkdf2()
- C. password_hash()
- D. crypt()
- E. openssl_digest()

ANSWER: A E

QUESTION NO: 12

Consider the following XML code:

PHP 5.5 in 42 Hours

Learning PHP 5.5 The Hard Way

Which of the following SimpleXML calls prints the name of the second book?

(Let `$xml = simplexml_load_file("books.xml");` .) (Choose 2)

- A. `echo $xml->books->book[2];`
- B. `echo $xml->books->book[1];`
- C. `echo $xml->book[1];`
- D. `echo $xml->xpath("/books/book[@id=2]");`
- E. `$c = $xml->children(); echo $c[1];`

ANSWER: C E

QUESTION NO: 13

Which of the following can be registered as entry points with a SoapServer instance (choose 2):

- A. A single function
- B. A single method from a class
- C. All methods from a class

D. All classes defined in a script

ANSWER: A C

QUESTION NO: 14

Your application uses PHP to accept and process file uploads. It fails to upload a file that is 5 MB in size, although `upload_max_filesize` is set to "10M". Which of the following configurations could be responsible for this outcome? (Choose 2)

- A. The PHP configuration option `post_max_size` is set to a value that is too small
- B. The web server is using an incorrect encoding as part of the HTTP response sent to the client
- C. The browser uses an incorrect encoding as part of the HTTP request sent to the server
- D. The hidden form field `MAX_FILE_SIZE` was set to a value that is too small
- E. PHP cannot process file uploads larger than 4 MB

ANSWER: A D

QUESTION NO: 15

Which one of the following XML declarations is NOT valid?

- A. `<?xml version="1.0" ?>`
- B. `<?xml version="1.1" encoding="UTF-8" ?>`
- C. `<?xml standalone="no" ?>`
- D. `<?xml standalone="1" ?>`

- A. Option A
- B. Option B
- C. Option C
- D. Option D

ANSWER: D