

# DUMPSARENA

## Certified Modular Integration Specialist exam

### [Hitachi HH0-200](#)

Total Questions: 10  
Version Demo

<https://dumpsarena.com>  
[sales@dumpsarena.com](mailto:sales@dumpsarena.com)

**QUESTION NO: 1**

A customer has received a shipment of a Hitachi Thunder 9570V Series subsystem. There is one RK and three RKA mounted on a 19" rack. Using the procedure in the Installation Manual, what is the correct combination of the x16 switch and the x1 switch settings to set the unit ID for the third RKA from the bottom?

- A. x16 is set to 0 and x1 is set to 3
- B. x16 is set to 4 and x1 is set to 0
- C. x16 is set to 0 and x1 is set to 4
- D. x1 is set to 3 and x16 is set to 0

**Answer: A**

**QUESTION NO: 2**

Click the Task button. Place the steps for installing the Rack Mount Model of the Hitachi Thunder 9500V Series subsystem in the correct order.

**Answer:**

**QUESTION NO: 3**

Which two statements are true about the separation of LUs from a Unified LUN on a Hitachi Thunder 9500V Series subsystem? (Choose two.)

- A. You can separate any LU from the Unified LUN.

- B. You can separate all the LUs from the Unified LUN.
- C. You can separate the last LU from the Unified LUN.
- D. You can separate all LUNs except two from the Unified LUN.

**Answer: B,C**

**QUESTION NO: 4**

Which of the following parts can be downgraded while the 9500V is online?

- A. RKA
- B. Drive
- C. Cache
- D. Controller

**Answer: B**

**QUESTION NO: 5**

You notice that the EALM LED on the controller is RED. What does this indicate?

- A. There is a fibre port failure.
- B. There is a controller failure.
- C. There is a cache DIMM failure.
- D. There is an error on the ENC board.

**Answer: D**

**QUESTION NO: 6**

What are the three modes of operation on Hitachi Resource Manager GUI? (Choose three.)

- A. Admin mode
- B. Normal mode
- C. Initial setup mode
- D. Maintenance mode
- E. Management mode

**Answer: B,D,E**

**QUESTION NO: 7**

A customer has a Hitachi Thunder 9532V subsystem in Hot Standby mode with the RAID configuration set up as (3D + 1P) x 2 and one spare drive. Which statement is true if the primary controller fails?

- A. Host access is interrupted due to controller failure.
- B. The system shuts down and waits for the failed controller to be replaced.
- C. Hot Standby controller takes over the LU access and the host receives an I/O error.
- D. Hot Standby controller takes over the LU access and there is no interruption on the host front.

**Answer: D**

**QUESTION NO: 8**

Which two statements are true about Hitachi FlashAccess software managing cache on a Hitachi Thunder 9500V Series subsystem? (Choose two.)

- A. Hitachi FlashAccess?is supported on a dual controller.
- B. Hitachi FlashAccess?is supported on a single controller.
- C. Hitachi FlashAccess?is supported only on RAID 5 and RAID 0+1 LUNs.
- D. Hitachi FlashAccess?is supported only on RAID 0, RAID 1, RAID 5, and RAID 0+1 LUNs.

**Answer: A,C**

**QUESTION NO: 9**

A customer needs 2 RKs and 5 RKAs installed in a Hitachi Data Systems?9?rack. What is the total EIA how many railkits does the customer need?

- A. 21U and 7 railkits
- B. 26U and 8 railkits
- C. 26U and 7 railkits
- D. 29.5U and 8 railkits

**Answer: A**

**QUESTION NO: 10**

Which DIMM size can be used for cache on a Hitachi Thunder 9530V?Series subsystem?

- A. 256MB
- B. 512MB
- C. 1GB
- D. 2GB

Answer: B

DUMPSARENA