



Hitachi Data Systems Storage Architect-Hitachi NAS Platform

[Hitachi HH0-450](#)

Total Questions: 10
Version Demo

<https://dumpsarena.com>
sales@dumpsarena.com

QUESTION NO: 1

A customer is asking for a detailed description of clustering technology on the Hitachi NAS Platform cluster with multiple GbE ports in the aggregates. Which two statements describe the automatic failover behavior? (Choose two.)

- A. Only the EVS affected by a problem will failover to another node.
- B. All EVS will failover when a GbE port in an aggregation fails.
- C. An EVS will failover when all GbE ports in an aggregation used by an EVS fail.
- D. An EVS will not failover when all GbE ports used by an EVS fail.

Answer: A,C

QUESTION NO: 2

Which three documents must be completed in the pre-sales cycle before scheduling professional services resources for a customer installation? (Choose three.)

- A. Pre-Qualification Questionnaire
- B. Site Implementation Guide
- C. Systems Assurance Document
- D. Pre-Engagement Checklist
- E. Change Control Approval Form

Answer: A,C,D

QUESTION NO: 3

An enterprise customer has a diverse Active Directory environment consisting of multiple untrusted departmental Windows domains. The customer wants to delegate administration to departmental administrators using the highest level of security. Which EVS security configuration will achieve this business requirement?

- A. Use the global EVS security context for all EVSs.
- B. Use an independent EVS security context for each EVSs.
- C. Use IPSEC for all EVSs to create secure client connections.
- D. Use SSL certificates to encrypt client communications.

Answer: B

QUESTION NO: 4

You are designing a solution with a Hitachi NAS Platform cluster connected to a Hitachi AMS2000 Family storage system with SAS disk drives. Which two actions will optimize performance? (Choose two.)

- A. Configure at least 4 LUNs per RAID group.
- B. Configure 1 LUN per RAID group.
- C. Disable superflush on each system drive.
- D. Set the correct superflush setting on each system drive.

Answer: B,D

QUESTION NO: 5

A customer would like to implement an OLTP application using their Hitachi NAS Platform 3200. The Hitachi NAS Platform is connected to a Hitachi AMS2300 with SAS drives. They want to achieve

maximum performance. Considering the queue depth limitations on the Hitachi NAS Platform and Hitachi AMS2000 family, what is the maximum number of active LUNs that must be assigned on each AMS port?

- A. 16
- B. 32
- C. 64
- D. 128

Answer: A

QUESTION NO: 6

A customer wants to discuss manual site failover design. The solution design must guarantee the replication of file system snapshots. What should the customer use?

- A. TrueCopy
- B. Intelligent Data Replication
- C. Incremental Data Replication
- D. Transfer Primary Access

Answer: A

QUESTION NO: 7

A customer has 28 independent file servers with various amounts of data on each server and they would like to consolidate with a Hitachi NAS Platform. Which three factors must be considered prior to the consolidation? (Choose three.)

- A. number of concurrent users
- B. type of applications and specific purpose of each application server
- C. server BIOS version
- D. number of mount points and shares
- E. number of concurrent HTTP instances

Answer: A,B,D

QUESTION NO: 8

An Internet Service Provider plans to purchase 32 2-node Hitachi NAS Platform 3090 for use in a managed service environment. They would like to dedicate one storage system to this environment. They would prefer a direct attached FCAL topology without having to use a fabric switch. And they would like to use Hitachi Dynamic Provisioning. Which two Hitachi storage systems would be used? (Choose two.)

- A. USP
- B. USP V
- C. VSP
- D. AMS2500

Answer: B,C

QUESTION NO: 9

A customer has implemented XVL with their Hitachi NAS platform and they are using their re-purposed NetApp Filers as XVL targets. The customer wants to ensure that their NDMP backups include the migrated files as part of the backup. What should you do?

- A. Add the environment variable `NDMP_BLUEARC_INCLUDE_MIGRATED -y`.

- B. Add the environment variable NDMP_BLUEARC_EXCLUDE_MIGRATED -y.
- C. Add the environment variable NDMP_BLUEARC_REMIGRATE -y.
- D. Use the default variable.

Answer: D

QUESTION NO: 10

A customer has asked you to plan a server migration from their existing Microsoft Windows storage server cluster to their Hitachi NAS platform. The customer requires that namespace be preserved so that the migration is transparent to their end-users. Which three actions will achieve the desired result? (Choose three.)

- A. Use CNAME records to preserve UNC paths on cut-over.
- B. Move the IP addresses to the EVSs from the original source server.
- C. Rename the EVS CIFS server name to the original source server name on cut-over.
- D. Change the UNC path in the logon scripts to point to the new server names given to the EVS CIFS server instances.
- E. Use DFS and link both the EVS CIFS server instances and the original servers to the same context.

Answer: A,C,D