DUMPSDOSS.

Certified Wireless Network Administrator

CWNP CWNA-107

Version Demo

Total Demo Questions: 6

Total Premium Questions: 118

Buy Premium PDF

https://dumpsboss.com

support@dumpsboss.com

dumpsboss.com



QUESTION NO: 1

When performing a validation survey for a Multiple Channel Architecture (MCA) system in a multi-tenant building with five floors, what aspect should you, as the surveyor, keep in mind?

- A. The RF interference caused by passing airplanes supporting on-board Wi-Fi should be a prime consideration
- **B.** The channel reuse pattern should be three dimensional with the RF cell extending coverage of each access point to other floors
- **C.** The omni-directional antennas of the access points should be oriented parallel to the floor to maximize the coverage pattern across as many floors as possible
- D. The Fresnel Zone is completely blocked between floors so each floor is considered a separate site survey

ANSWER: B

QUESTION NO: 2

During a post-implementation survey, you have detected a non-802.11 wireless device transmitting in the area used by handheld 802.11g scanners. What is the most important factor in determining the impact of this non-802.11 device?

- A. Protocols utilized
- B. Channel occupied
- C. Receive sensitivity
- D. Airtime utilization

ANSWER: B

QUESTION NO: 3

Which unit of measurement is an absolute unit that is used to quantify received signal power levels on a logarithmic scale?

- A. dBm
- B. SNR
- C. RSSI
- D. VSWR



ANSWER: A

QUESTION NO: 4

You are attempting to locate the cause of a performance problem in two WLAN cells in a mostly overlapping coverage area. You note that one AP is on channel 1 and the other is on channel 2. When you document your findings, what term do you use to describe the problem in this configuration?

- A. Bluetooth interference
- B. Non-Wi-Fi interference
- C. CCI
- D. ACI

ANSWER: C D

QUESTION NO: 5

A non-802.11 device is suspected of causing interference on the WLAN. You are not certain of the location or type of device. What is the best solution for locating this non-802.11 device?

- A. Access point spectrum analyzer
- B. Laptop-based spectrum analyzer with an omni-directional antenna
- **C.** Laptop-based spectrum analyzer with a directional antenna.
- **D.** Laptop-based spectrum analyzer with an omni-directional antenna.

ANSWER: A

QUESTION NO: 6

An IEEE 802.11 amendment is in the daft state. What impact does this draft amendment have on the 802.11 standard?

- **A.** No impact: Until an amendment is ratified, it does not become part of the standard.
- **B.** Devices will be released based on the draft amendment and the draft amendment features are part of the standard.
- C. The standard is changed to reflect the new capabilities as soon as an amendment enters the draft stage.
- **D.** No impact: Draft amendments do not become part of the standard until a working group is formed.

