

DUMPSBOSS.COM

Check Point Certified Security Master

Checkpoint 156-115.77

Version Demo

Total Demo Questions: 15

Total Premium Questions: 295

Buy Premium PDF

<https://dumpsboss.com>

support@dumpsboss.com

dumpsboss.com

Topic Break Down

Topic	No. of Questions
Topic 1, Chain Modules	27
Topic 2, NAT	25
Topic 3, ClusterXL	35
Topic 4, VPN Troubleshooting	27
Topic 5, SecureXL Acceleration debugging	24
Topic 6, Hardware Optimization	33
Topic 7, Software Tuning	16
Topic 8, Enable CoreXL	16
Topic 9, IPS	30
Topic 10, IPV6	15
Topic 11, Advanced VPN	47
Total	295

QUESTION NO: 1

What are the kernel parameters that control "Magic MACs"?

- A. fwaha_magic_mac and fw_forward_magic_mac
- B. fwaha_mac_magic and fw_mac_forward_magic
- C. cpha_mac_magic and cp_mac_forward_magic
- D. cpha_magic_mac and cpha_mac_forward_magic

ANSWER: B

QUESTION NO: 2

In a VPN configuration, the following mode can be used to increase throughput by bypassing firewall enforcement.

- A. Virtual Tunnel Interface (VTI) Mode can bypass firewall for all encrypted traffic
- B. Hub Mode can be used to bypass stateful inspection
- C. There is no such mode that can bypass firewall enforcement
- D. Wire mode can be used to bypass stateful inspection

ANSWER: D

QUESTION NO: 3

How would one enable 'INSPECT debugging' if one suspects IPS false positives?

- A. Run command fw ctl set int enable_inspect_debug 1 from the command line.
- B. Toggle the checkbox in Global Properties > Firewalls > Inspection section.
- C. WebUI
- D. Set the following parameter to true using GuiDBedit:
enable_inspect_debug_compilation.

ANSWER: D

QUESTION NO: 4

In IPS what does a high confidence rating mean?

- A. This is a rating for how confident Check Point is with catching this attack
- B. This is a rating for how likely this attack is to penetrate most systems
- C. There is a high likelihood of false positives
- D. There is a low likelihood of false positives

ANSWER: D

QUESTION NO: 5

How do you set up Port Address Translation?

- A. Since Hide NAT changes to random high ports it is by definition PAT (Port Address Translation).
- B. Create a manual NAT rule and specify the source and destination ports.
- C. Edit the service in SmartDashboard, click on the NAT tab and specify the translated port.
- D. Port Address Translation is not support in Check Point environment

ANSWER: B

QUESTION NO: 6

Since R76 GAiA, what is the method for configuring proxy ARP entries for manual NAT rules?

- A. WebUI or add proxy ARP ... commands via CLISH
- B. SmartView Tracker
- C. local.arp file
- D. SmartDashboard

ANSWER: A

QUESTION NO: 7

For URL Filtering in the Cloud in R75 and above, what table is used to contain the URL

Filtering cache values?

- A. urlf_blade_on_gw
- B. urlf_cache_tbl
- C. urlf_cache_table
- D. url_scheme_tab

ANSWER: C**QUESTION NO: 8**

Your gateway object is currently defined with a max connection count of 25k connections in Smart Dashboard. Which of the following commands would show you the current and peak connection counts?

- A. show connections all
- B. fw ctl conn
- C. fw ctl chain
- D. fw ctl pstat

ANSWER: D**QUESTION NO: 9**

The command that lists the firewall kernel modules on a Security Gateway is:

- A. fw list kernel modules
- B. fw ctl kernel chain
- C. fw ctl debug -m
- D. fw list modules

ANSWER: C

QUESTION NO: 10

PXL is considered to be what type of acceleration?

- A. Fast Path
- B. Slow Path
- C. Medium Path
- D. PXL is not related to acceleration

ANSWER: C

QUESTION NO: 11

You are having issues with dynamic routing after a failover. The traffic is now coming from the backup and is being dropped as out of state. What is the BEST configuration to avoid stateful inspection dropping your dynamic routing traffic?

- A. Implement Wire mode.
- B. In Global Properties select Accept other IP protocols stateful replies for unknown services.
- C. Enable Visitor mode.
- D. Create additional explicit rules.

ANSWER: A

QUESTION NO: 12

What does the command `vpn shell interface add numbered 192.168.0.1 192.168.0.2`

Gateway_A to_B accomplish?

- A. Between Security Gateways A and B, 192.168.0.1 is assigned as the endpoint IP address to Gateway A 192.168.0.2 is assigned to Gateway B
- B. Between Security Gateways A and B 192.168.0.2 is assigned as the endpoint IP address to Gateway A 192.168.0.1 is assigned to Gateway B
- C. shell is not a valid option for the command vpn.
- D. This command can be used to create a VPN tunnel from the command line without having any VPN configuration in Smart Dashboard (although "IPSec VPN" must still be enabled on the gateway).

ANSWER: A**QUESTION NO: 13**

From the output of the following cphaprob -i list, what is the most likely cause of the clustering issue?

Cluster B> cphaprob -i list

Built-in Devices:

Device Name: Interface Active Check Current state: OK

Device Name: HA Initialization Current state: OK

Device Name: Recovery Delay Current state: OK

Registered Devices:

Device Name: Synchronization Registration number: 0 Timeout: none Current state: OK

Time since last report: 3651.5 sec

Device Name: Filter Registration number: 1 Timeout: none Current state: problem Time since last report: 139 sec

Device Name: routed Registration number: 2 Timeout: none Current state: OK Time since last report: 3651.9 sec

Device Name: cphad Registration number: 3 Timeout: none Current state: OK Time since last report: 3696.5 sec

Device Name: fwd Registration number: 4 Timeout: none Current state: OK Time since last report: 3696.5 sec

- A. There is an interface down on Cluster A
- B. There is a sync network issue between Cluster A and Cluster B
- C. The routing table on Cluster B is different from Cluster A
- D. Cluster B and Cluster A have different versions of policy installed.

ANSWER: D**QUESTION NO: 14**

Where would an administrator set an email alert for a specific permanent VPN tunnel?

- A. Edit the file vpnconf.
- B. Run sysconfig.
- C. In the Tunnel Properties select Mail Alert.

D. You can only enable logging or SNMP traps.

ANSWER: C

Explanation:

:

C1102 - Advanced VPN

QUESTION NO: 15

Which feature is not supported with unnumbered VTI?

- A. Proxy interfaces
- B. High availability
- C. Policy based routing
- D. Anti-spoofing

ANSWER: D